

**6 3/4" PBL DUAL PORT BYPASS SYSTEM
TECHNICAL SHEET**

SERIAL #	_____	*
A-TOOL O.D.	_____	6.75"
B-TOOL I.D. (DRIFT)	_____	1.25"
FLOW AREA THROUGH TOOL	_____	2.92 sq./in.
C-BOX CONNECTION	_____	4 1/2 IF
D-PIN CONNECTION	_____	4 1/2 IF
E-ACTIVATION BALL: DIAMETER	_____	2"
MATERIAL	_____	Ertalyte
NUMBER OF BALLS TO ACTIVATE	_____	1
BALL SHEARING PRESSURE F-DEACTIVATION BALL: DIAMETER	_____	As Desired
MATERIAL	_____	1 3/8"
NUMBER OF BALLS TO DEACTIVATE	_____	Chrome Steel
G-SIZE OF PORT	_____	2
NUMBER OF PORTS	_____	1.25"
TFA WHEN TOOL IS OPEN	_____	2
NUMBER OF CYCLES	_____	2.454 sq./in.
OVERALL LENGTH	_____	5
WEIGHT	_____	8 - 9 ft
TENSILE STRENGTH	_____	692 lbs
TORSIONAL STRENGTH	_____	3,100,000 lbs
MAKE UP TORQUE	_____	190,000 ft/lbs
		34,840 ft/lbs

NOTES:

NO DRIFT WHEN BALLS ARE IN TOOL.

*Tools are rated to operate in temp. up to 420 degrees Fahrenheit.

