

**9 1/2" PBI SLIDING SLEEVE BIG BORE
TECHNICAL SHEET**

9 1/2" O.D.

SERIAL #	_____	*
A-TOOL O.D.	_____	9 1/2"
B-TOOL I.D. (DRIFT)	_____	2.63"
FLOW AREA THROUGH TOOL	_____	5.43 sq./in.
C-BOX CONNECTION	_____	6 5/8 reg
D-PIN CONNECTION	_____	6 5/8 reg
E-ACTIVATION DART:		
DIAMETER	_____	2.67"
MATERIAL	_____	STAINLESS
NUMBER OF DARTS TO ACTIVATE	_____	1
BALL SHEARING PRESSURE	_____	NA
F-DEACTIVATION BALL:		
DIAMETER	_____	NA
MATERIAL	_____	NA
NUMBER OF BALLS TO DEACTIVATE	_____	NA
G-SIZE OF PORT	_____	1.50"
NUMBER OF PORTS	_____	2
TFA WHEN TOOL IS OPEN	_____	3.534 sq./in.
NUMBER OF CYCLES	_____	UNLIMITED
OVERALL LENGTH	_____	5 ft
WEIGHT	_____	750 lbs
TENSILE STRENGTH	_____	3,700,000 lbs
TORSIONAL STRENGTH	_____	335,000 ft/lbs
MAKE UP TORQUE	_____	46,450 ft/lbs

NOTES:

NO DRIFT WHEN DART IS IN TOOL.

*Tools are rated to operate in temp. up to 420 degrees Fahrenheit.

*2.44" Drift, 2.48" Dart also Available

*

